



# AP FAST REPAIR 850 – A

## SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

### Product Identifier

Product Name AP FAST REPAIR 850 – A

Recommended use of the chemical and restrictions on use  
Part A of two component, polyurethane system.

### Supplier Details

Name Alchatek  
Address 4508 Bibb Blvd  
Tucker, GA 30084

Telephone (404) 618-0438

### Emergency Phone Numbers

Call CHEMTREC Day or Night  
1-800-424-9300  
+1 703-527-3887

## SECTION 2: HAZARDS IDENTIFICATION

### GHS Classification of the substance or mixture

Acute Tox.	4	Acute toxicity
Eye Dam./Irritant	2B	Serious eye damage/eye irritation
Skin Corr./Irritant	2	Skin corrosion/irritation
Skin Sens.	1B	Skin sensitization
Resp. Sens.	1	Respiratory sensitization
STOT SE	3	Specific target organ toxicity — single exposure respiratory system
STOT SE	2	Specific target organ toxicity — repeated exposure.

## AP FAST REPAIR 850 – A

### GHS Label elements

#### Hazard pictograms/symbols



Signal word:       Warning

#### Hazard statements:

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H320 Causes eye irritation.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H373 May cause damage to organs (Olfactory organs) through prolonged or repeated exposure (inhalation).

#### Precautionary statements:

- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P271 Use only outdoors or in a well-ventilated area.
- P260 Do not breathe dust/gas/mist/vapours.
- P261 Avoid breathing mist.
- P202 Do not handle until all safety precautions have been read and understood.
- P284 [In case of inadequate ventilation] wear respiratory protection.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P264 Wash with plenty of water and soap thoroughly after handling.
- P312 Call a POISON CENTER or doctor/physician if you feel unwell.
- P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P314 Get medical advice/attention if you feel unwell.
- P303 + P352 IF ON SKIN (or hair): Wash with plenty of soap and water.
- P333 + P311 If skin irritation or rash occurs: Call a POISON CENTER or doctor/physician.
- P362 + P364 Take off contaminated clothing and wash before reuse.
- P332 + P313 If skin irritation occurs: Get medical advice/attention.
- P337 + P311 If eye irritation persists: Call a POISON CENTER or doctor/physician.
- P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
- P501 Dispose of contents/container to hazardous or special waste collection point.

**Additional information:**

Labeling of special preparations (GHS):

CONTAINS ISOCYANATES. INHALATION OF ISOCYANATE MISTS OR VAPORS MAY CAUSE RESPIRATORY IRRITATION, BREATHLESSNESS, CHEST DISCOMFORT AND REDUCED PULMONARY FUNCTION. OVEREXPOSURE WELL ABOVE THE PEL MAY RESULT IN BRONCHITIS, BRONCHIAL SPASMS AND PULMONARY EDEMA. LONGTERM EXPOSURE TO ISOCYANATES HAS BEEN REPORTED TO CAUSE LUNG DAMAGE, INCLUDING REDUCED LUNG FUNCTION WHICH MAY BE PERMANENT. ACUTE OR CHRONIC OVEREXPOSURE TO ISOCYANATES MAY CAUSE SENSITIZATION IN SOME INDIVIDUALS, RESULTING IN ALLERGIC RESPIRATORY REACTIONS INCLUDING WHEEZING, SHORTNESS OF BREATH AND DIFFICULTY BREATHING. ANIMAL TESTS INDICATE THAT SKIN CONTACT MAY PLAY A ROLE IN CAUSING RESPIRATORY SENSITIZATION.

**HMIS Rating:**

Health: 2  
 Flammability: 1  
 Physical Hazard: 0

**SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS**

Mixture

Description: Mixture of substances listed below with nonhazardous additions.

Name	CAS NO.	% wt/wt
POLYMETHYLENE POLYPHENYLISOCYANATE	Trade Secret	75-100%

**SECTION 4: FIRST-AID MEASURES**

Description of first aid measures

General advice: Remove contaminated clothing.

If inhaled: Remove the affected individual into fresh air and keep the person calm. Assist in breathing if necessary. Immediate medical attention required.

If on skin: Wash affected areas thoroughly with soap and water. If irritation develops, seek medical attention.

If in eyes: In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water. Immediate medical attention required.

If swallowed: Rinse mouth and then drink plenty of water. Do not induce vomiting. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Immediate medical attention required.

**Most important symptoms and effects, both acute and delayed:**

Symptoms: The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11., Eye irritation, skin irritation, allergic symptoms

Hazards: Symptoms can appear later.

Information on: Diphenylmethane-4,4'-diisocyanate (MDI)

Hazards: Respiratory sensitization may result in allergic (asthma-like) signs in the lower respiratory tract including wheezing, shortness of breath and difficulty breathing, the onset of which may be delayed. Repeated inhalation of high concentrations may cause lung damage, including reduced lung function, which may be permanent. Substances eliciting lower respiratory tract irritation may worsen the asthma-like reactions that may be produced by product exposures.

**Indication of any immediate medical attention and special treatment needed:**

Note to physician **Antidote:** Specific antidotes or neutralizers to isocyanates do not exist.

**SECTION 5: FIRE-FIGHTING MEASURES (ERG CODE 171)**

**Extinguishing media**

Suitable extinguishing agents: water spray, dry powder, carbon dioxide, foam

**Specific hazards arising from the substance or mixture:**

Hazards during fire-fighting: nitrous gases, fumes/smoke, isocyanate, vapour

### Advice for the firefighters

Protective equipment:	Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.
Additional information:	Keep containers cool by spraying with water if exposed to fire. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

### SECTION 6: ACCIDENTAL RELEASE MEASURES (ERG CODE 171)

Personal precautions, protective equipment and emergency procedures:	Clear area. Ensure adequate ventilation. Wear suitable personal protective clothing and equipment
Environmental precautions:	Do not discharge into drains/surface waters/groundwater.
Methods and material for containment and cleaning up:	<b>For small amounts:</b> Absorb isocyanate with suitable absorbent material (see § 40 CFR, sections 260, 264 and 265 for further information). Shovel into open container. Do not make container pressure tight. Move container to a well-ventilated area (outside). Spill area can be decontaminated with the following recommended decontamination solution: Mixture of 90 % water, 8 % concentrated ammonia, 2 % detergent. Add at a 10 to 1 ratio. Allow to stand for at least 48 hours to allow escape of evolved carbon dioxide.

### SECTION 7: HANDLING AND STORAGE

Precautions for safe handling:	Provide suitable exhaust ventilation at the processing machines. Ensure thorough ventilation of stores and work areas. Avoid aerosol formation. When handling heated product, vapours of the product should be ventilated, and respiratory protection used. Wear respiratory protection when spraying. Danger of bursting when sealed gastight. Protect against moisture. If bulging of drum occurs, transfer to well ventilated area, puncture to relieve pressure, open vent and let stand for 48 hours before resealing. Store in cool, dry place in tightly closed receptacles (60-80°F recommended).
--------------------------------	---

**AP FAST REPAIR 850 – A**

Conditions for safe storage, including any incompatibilities:

Keep away from water. Segregate from foods and animal feeds. Segregate from acids and bases. Segregate from bases.

Further Information about storage conditions:

Formation of CO<sub>2</sub> and build up of pressure possible. Keep container tightly closed and in a well-ventilated place. Outage of containers should be filled with dry inert gas at atmospheric pressure to avoid reaction with moisture.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Control parameters**

**Components with occupational exposure limits**

Diphenylmethane-4,4'-diisocyanate (MDI)	OSHA PEL	CLV 0.02 ppm 0.2 mg/m <sup>3</sup> ; CLV 0.02 ppm 0.2 mg/m <sup>3</sup> ;
	ACGIH TLV	TWA value 0.005 ppm ;
P-MDI	OSHA PEL	CLV 0.02 ppm 0.2 mg/m <sup>3</sup> ; CLV 0.02 ppm 0.2 mg/m <sup>3</sup> ;
	ACGIH TLV	TWA value 0.005 ppm
Isocyanic acid, polymethylenepolyphenylene ester (P-MDI)	OSHA PEL	CLV 0.02 ppm 0.2 mg/m <sup>3</sup> ; CLV 0.02 ppm 0.2 mg/m <sup>3</sup>
	ACGIH TLV	TWA value 0.005 ppm ;

**Engineering controls**

Provide readily accessible eye wash stations and safety showers. Provide ventilation adequate to ensure concentrations are minimized.

**Personal protective equipment**

General protective and hygienic measures:

Wear protective clothing as necessary to prevent contact. Eye wash fountains and safety showers must be easily accessible. Observe the appropriate PEL or TLV value. Wash soiled clothing immediately. Contaminated equipment or clothing should be cleaned after each use or disposed of.

Respiratory protection:	When workers are facing concentrations above the occupational exposure limits they must use appropriate certified respirators. When atmospheric levels may exceed the occupational exposure limit (PEL or TLV) NIOSH-certified air-purifying respirators equipped with an organic vapor sorbent and particulate filter can be used as long as appropriate precautions and change out schedules are in place. For emergency or non-routine, high exposure situations, including confined space entry, use a NIOSH-certified full facepiece pressure demand self-contained breathing apparatus (SCBA) or a full facepiece pressure demand supplied-air respirator (SAR) with escape provisions.
Hand protection:	Chemical resistant protective gloves should be worn to prevent all skin contact. Suitable materials may include, chloroprene rubber (Neoprene), nitrile rubber (Buna N), chlorinated polyethylene, polyvinylchloride (Pylox), butyl rubber, depending upon conditions of use.
Eye protection:	Tightly fitting safety goggles (chemical goggles). Wear face shield if splashing hazard exists.
Skin and Body protection:	Cover as much of the exposed skin as possible to prevent all skin contact. Suitable materials may include, saran-coated material, depending upon conditions of use.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### General Information

Appearance	
Form:	Liquid
Colour:	Dark Amber
Odour:	Faint aromatic
Odour threshold:	No data available
pH:	No data available
Melting point/range:	< 0 °C
Boiling point/range:	> 200 °C
Flash point:	> 200 °C
Evaporation rate:	No data available

Flammability (solid, gaseous):	Not applicable
Upper/lower flammability or explosive limit:	Not applicable
Vapor pressure:	No data available
Vapor density:	No data available
Relative Density at 20°C:	1.23 g/cm <sup>3</sup>
Solubility in / Miscibility with Water:	Reacts with water
Partition coefficient (n-octanol/water):	No data available
Auto/Self-ignition temperature:	No data available
Decomposition temperature:	No data available
Viscosity	

## SECTION 10: STABILITY AND REACTIVITY

### Reactivity:

Corrosion to metals: No corrosive effect on metal.

### Chemical stability

Thermal decomposition / conditions to be avoided: No decomposition if used and stored according to specifications.

Possibility of hazardous reactions: Reacts with water, with formation of carbon dioxide. Risk of bursting. Reacts with alcohols. Reacts with acids. Reacts with alkalis. Reacts with amines. Risk of exothermic reaction. Risk of polymerization. Contact with certain rubbers and plastics can cause brittleness of the substance/product with subsequent loss in strength.

Conditions to avoid: **Avoid moisture.**

Incompatible materials: Acids, amines, alcohols, water, Alkalines, strong bases, Substances/products that react with isocyanates.

Hazardous decomposition products: Hazardous decomposition products: carbon monoxide, carbon dioxide, nitrogen oxide, hydrogen cyanide, nitrogen oxides, aromatic isocyanates, gases/vapours



## SECTION 11: TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure:

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

### Symptoms related to physical, chemical and toxicological characteristics:

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11. Eye irritation, skin irritation, allergic symptoms.

### Medical conditions aggravated by overexposure

The isocyanate component is a respiratory sensitizer. It may cause allergic reaction leading to asthma-like spasms of the bronchial tubes and difficulty in breathing. Medical supervision of all employees who handle or come into contact with isocyanates is recommended. Contact may aggravate pulmonary disorders. Persons with history of respiratory disease or hypersensitivity should not be exposed to this product. Preemployment and periodic medical examinations with respiratory function tests (FEV, FVC as a minimum) are suggested. Persons with asthmatic conditions, chronic bronchitis, other chronic respiratory diseases, recurrent eczema or pulmonary sensitization should be excluded from working with isocyanates. Once a person is diagnosed as having pulmonary sensitization (allergic asthma) to isocyanates, further exposure is not recommended.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure:

Assessment of repeated dose toxicity: The substance may cause damage to the olfactory epithelium after repeated inhalation. The substance may cause damage to the lung after repeated inhalation. These effects are not relevant to humans at occupational levels of exposure.

### Numerical measures of toxicity:

#### Oral

Information on:	Diphenylmethane-4,4'-diisocyanate (MDI)
Type of value:	LD50
Species:	rat (male/female)
Value:	> 2,000 mg/kg (Directive 84/449/EEC, B.1)

#### Inhalation

Type of value:	LC50
Species:	rat (male/female)
Value:	2.0 mg/l (OECD Guideline 403) An aerosol was tested.

## Dermal

Information on:	Diphenylmethane-4,4'-diisocyanate (MDI)
Type of value:	LD50
Species:	rabbit (male/female)
Value:	> 9,400 mg/kg

## SECTION 12: ECOLOGICAL INFORMATION

### Aquatic toxicity:

#### Assessment of aquatic toxicity:

There is a high probability that the product is not acutely harmful to aquatic organisms. The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations. Based on long-term (chronic) toxicity study data, the product is very likely not harmful to aquatic organisms. The product may hydrolyse. The test result may be partially due to degradation products. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

#### Toxicity to fish

LC0 (96 h) > 1,000 mg/l, *Brachydanio rerio* (OECD Guideline 203, static)

#### Aquatic invertebrates

EC50 (24 h) > 1,000 mg/l, *Daphnia magna* (OECD Guideline 202, part 1, static)

#### Aquatic plants

EC0 (72 h) 1,640 mg/l (growth rate), *Scenedesmus subspicatus* (OECD Guideline 201, static)

Persistence and degradability: Poorly biodegradable. The product is unstable in water. The elimination data also refer to products of hydrolysis.

Bioaccumulative potential: No data available on the product itself.

Mobility in soil: No data available.

Other adverse effects: No further relevant information available

**SECTION 13: DISPOSAL CONSIDERATIONS**

**Waste treatment methods**

Waste from residue/unused product:	This product should not be allowed to enter drains, water courses or the soil. Dispose of this material in a safe manner and in accordance with federal, state and local regulations.
Contaminated packaging:	Disposal must be made in accordance with official federal, state and local regulations.

**SECTION 14: TRANSPORT INFORMATION**

DOT:	Not classified as a dangerous good under transport regulations
IMDG:	Not classified as a dangerous good under transport regulations
IATA:	Not classified as a dangerous good under transport regulations

**SECTION 15: REGULATORY INFORMATION**

Safety, health and environmental regulations/legislation specific for the substance or mixture.

**Federal Regulations**

**Registration status:**

Chemical TSCA, US released / listed

EPCRA 311/312 (Hazard categories): Acute; Chronic

EPCRA 313:	CAS Number	Chemical name
	101-68-8	Diphenylmethane-4,4'-diisocyanate (MDI)
CERCLA RQ	CAS Number	Chemical name
5000 LBS 1	01-68-8	Diphenylmethane-4,4'-diisocyanate (MDI)

**State regulations**

State RTK	CAS Number	Chemical name
NJ	26447-40-5	Methylenediphenyl-diisocyanate
MA, NJ, PA 1	01-68-8	Diphenylmethane-4,4 -diisocyanate (MDI)

## SECTION 16: OTHER INFORMATION

### Legend to abbreviations used in the safety data sheet:

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

### Abbreviation and acronyms:

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road
IMDG:	International Maritime Code for Dangerous Goods
DOT:	US Department of Transportation
IATA:	International Air Transport Association
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals
ACGIH:	American Conference of Governmental Industrial Hygienist.
EINECS:	European Inventory of Existing Commercial Chemical Substances
ELINCS:	European List of Notified Chemical Substance
CAS:	Chemical Abstracts Service (division of the American Chemical Society)
HMIS:	Hazardous Materials Identification System (USA)
WHMIS:	Workplace Hazardous Materials Information System (Canada)

May, 2018

This SDS is on a three year review cycle. If the date on this sheet is older than three years please contact Alchatek for an updated SDS.

### Further information/disclaimer

DISCLAIMER: The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigation to determine the suitability of information for their particular purposes. In no event shall Alchatek be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, whatsoever arising, even if Alchatek has been advised of the possibility of such damages.



# AP FAST REPAIR 850 – B

## SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

### Product Identifier

Product Name AP FAST REPAIR 850 – B

**Recommended use of the chemical and restrictions on use**  
Part B of two component, polyurethane system.

### Supplier Details

Name Alchatek  
Address 4508 Bibb Blvd  
Tucker, GA 30084

Telephone (404) 618-0438

### Emergency Phone Numbers

Call CHEMTREC Day or Night  
1-800-424-9300  
+1 703-527-3887

## SECTION 2: HAZARDS IDENTIFICATION

### GHS Classification of the substance or mixture

Skin Irritant 2;	H315: Causes skin irritation.
Eye Irritant 2;	H319: Causes serious eye irritation.
Skin Sensitizer 1;	H317: May cause an allergic skin reaction.
Carcinogenicity 2;	H351: Suspected of causing cancer.
Aspiration Hazard 1;	H304: May be fatal if swallowed and enters airways.

## AP FAST REPAIR 850 – B

### GHS Label elements

#### Hazard pictograms/symbols



Signal word: Warning

#### Hazard statements:

H304: May be fatal if swallowed and enters airways.  
H315: Causes skin irritation.  
H319: Causes serious eye irritation.  
H317: May cause an allergic skin reaction.  
H351: Suspected of causing cancer.

#### Precautionary statements:

P280: wear protective gloves / eye protection.  
P273: Avoid release to the environment.  
P264: Wash thoroughly after handling.  
P261: Avoid breathing mist/vapours/spray.  
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes.  
Remove contact lenses, if present and easy to do. Continue rinsing.  
P333+P313: If skin irritation or rash occurs: Get medical advice/attention.  
P337+P313: If eye irritation persists: Get medical advice/attention.  
P501: Dispose of contents/container to hazardous or special waste collection point.

#### Additional information:

Contains epoxy constituents. May produce an allergic reaction.

#### HMIS Rating:

Health: 2  
Flammability: 1  
Physical Hazard: 0

**SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS**

Mixture

**Description:** Mixture of substances listed below with nonhazardous additions.

Name	CAS NO.	% wt/wt
Polyol blend	Trade Secret	60-90%
Aromatic Hydrocarbon Blend	68477-30- 5	<10%

In conformity with 29CFR 1910.1200(i) the specific chemical identity may be withheld as Trade Secret, while all health/safety properties and effects are included in the SDS.

**SECTION 4: FIRST-AID MEASURES**

**Description of first aid measures**

- General advice: Remove contaminated clothing.
- If inhaled: Remove the affected individual into fresh air and keep the person calm. Assist in breathing if necessary. Immediate medical attention required.
- If on skin: Wash affected areas thoroughly with soap and water. If irritation develops, seek medical attention.
- If in eyes: In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water. Immediate medical attention required.
- If swallowed: Rinse mouth and then drink plenty of water. Do not induce vomiting. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Immediate medical attention required.

**Most important symptoms and effects, both acute and delayed:**

- Acute: May cause allergic skin reaction with symptoms of reddening, itching, swelling, and rash. May cause skin irritation with symptoms of reddening, itching, and swelling. May cause eye irritation with symptoms of reddening, tearing, stinging, and swelling. May cause respiratory tract irritation with symptoms of coughing, sore throat and runny nose.

**Indication of any immediate medical attention and special treatment needed:**

None known.

## **SECTION 5: FIRE-FIGHTING MEASURES (ERG CODE 171)**

### Extinguishing media

Suitable extinguishing agents: water spray, dry powder, carbon dioxide, foam

### Specific hazards arising from the substance or mixture:

Hazards during fire-fighting: nitrous gases, fumes/smoke, isocyanate, vapour

### Advice for the firefighters

Protective equipment: Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Additional information: Keep containers cool by spraying with water if exposed to fire. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES (ERG CODE 171)**

Personal precautions, protective equipment and emergency procedures: Clear area. Ensure adequate ventilation. Wear suitable personal protective clothing and equipment.

Environmental precautions: Do not discharge into drains/surface waters/groundwater.

Methods and material for containment and cleaning up: Evacuate and keep unnecessary people out of spill area. Cleanup personnel must use appropriate personal protective equipment. Cover spill with inert material (e. g., dry sand or earth) and collect for proper disposal. Prevent from entering open drains and waterways.

## **SECTION 7: HANDLING AND STORAGE**

Precautions for safe handling: Avoid contact with skin or clothing. Avoid contact with eyes. Use only with adequate ventilation/personal protection. Wash thoroughly after handling. Keep container closed when not in use. Do not breathe vapours or spray mist. Store in a dry place away from excessive heat. Material is hygroscopic and may absorb small amounts of atmospheric moisture. Do not reseal container if contamination is suspected.).



Conditions for safe storage, including any incompatibilities:

Oxidizing agents, Acids, Isocyanates

Further Information about storage conditions:

Formation of CO<sub>2</sub> and build up of pressure possible. Keep container tightly closed and in a well-ventilated place. Outage of containers should be filled with dry inert gas at atmospheric pressure to avoid reaction with moisture.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

Exposure Limits (Components):

Country specific exposure limits have not been established or are not applicable

Engineering controls

Provide readily accessible eye wash stations and safety showers. Provide ventilation adequate to ensure concentrations are minimized.

### Personal protective equipment

General protective and hygienic measures:

Wear protective clothing as necessary to prevent contact. Eye wash fountains and safety showers must be easily accessible. Observe the appropriate PEL or TLV value. Wash soiled clothing immediately. Contaminated equipment or clothing should be cleaned after each use or disposed of. General dilution and local exhaust ventilation as necessary to control airborne vapors, aerosols (e.g., dusts, mists) and thermal decomposition products. Heating may result in generation of airborne vapors and/or aerosols.

Hand Protection:

Permeation resistant gloves, Viton gloves, 4H laminate gloves, Butyl rubber gloves, Nitrile rubber gloves.

Eye Protection:

Chemical safety goggles or safety glasses with side-shields., Chemical safety goggles in combination with a full face shield if a splash hazard exists.

Skin Protection:

Avoid all skin contact. Depending on the conditions of use, cover as much of the exposed skin area as possible with appropriate clothing to prevent skin contact., Where spray mist/vapor is anticipated, permeation resistant clothing is recommended.

Additional Protective Measures:

Employees should wash their hands and face before eating, drinking, or using tobacco products. Educate and train employees in the safe use and handling of this product. Emergency showers and eye wash stations should be available.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

### General Information

#### Appearance

Form:	Liquid
Colour:	Gray
Odour:	Slight
Odour threshold:	No data available
pH:	No data available
Melting point/range:	< 0 °C
Boiling point/range:	> 302 °F / > 150 °C
Flash point:	> 200 °F / > 93°C
Evaporation rate:	No data available
Flammability (solid, gaseous):	Not applicable
Upper/lower flammability or explosive limit:	Not applicable
Vapor pressure:	No data available
Vapor density:	No data available
Relative Density at 20°C:	1.06 g/cm <sup>3</sup>
Solubility in / Miscibility with Water:	Reacts with water
Partition coefficient (n-octanol/water):	No data available
Auto/Self-ignition temperature:	No data available
Decomposition temperature:	No data available
Viscosity	300-600 cps

## SECTION 10: STABILITY AND REACTIVITY

#### Reactivity:

Corrosion to metals: No corrosive effect on metal.

#### Chemical stability

Thermal decomposition / conditions to be avoided: No decomposition if used and stored according to specifications.

Possibility of hazardous reactions: Reacts with water.

Conditions to avoid:	Avoid extreme heat.
Incompatible materials:	Oxidizing agents, Acids, Isocyanates.
Hazardous decomposition products:	By Fire and Thermal Decomposition: Carbon oxides, Nitrogen oxides (NOx), Amines, other aliphatic fragments which have not been determined, Ammonia gas may be liberated at high temperatures.

## SECTION 11: TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure:

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

### Symptoms related to physical, chemical and toxicological characteristics:

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11. Eye irritation, skin irritation, allergic symptoms.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure:

Assessment of repeated dose toxicity: The substance may cause damage to the olfactory epithelium after repeated inhalation. The substance may cause damage to the lung after repeated inhalation. These effects are not relevant to humans at occupational levels of exposure.

### Numerical measures of toxicity:

None available for mixture itself

## SECTION 12: ECOLOGICAL INFORMATION

### Aquatic toxicity:

Assessment of aquatic toxicity: No data available on the product itself.

Persistence and degradability: Poorly biodegradable. The product is unstable in water. The elimination data also refer to products of hydrolysis.

Bioaccumulative potential: No data available on the product itself.

Mobility in soil: No data available on the product itself.

Other adverse effects: No further relevant information available.

**SECTION 13: DISPOSAL CONSIDERATIONS**

Waste treatment methods

Waste from residue/unused product:	This product should not be allowed to enter drains, water courses or the soil. Dispose of this material in a safe manner and in accordance with federal, state and local regulations.
Contaminated packaging:	Disposal must be made in accordance with official federal, state and local regulations.

**SECTION 14: TRANSPORT INFORMATION**

DOT	Not classified as a dangerous good under transport regulations
IATA	Not classified as a dangerous good under transport regulations
IMDG	Not classified as a dangerous good under transport regulations

**SECTION 15: REGULATORY INFORMATION**

Federal Regulations

Registration status:	Chemical TSCA, US released / listed	
EPCRA 311/312 (Hazard categories):	Acute; Chronic	
EPCRA 313:	<b>CAS Number</b>	<b>Chemical name</b>
	101-68-8	Diphenylmethane-4,4'-diisocyanate (MDI)
CERCLA RQ	<b>CAS Number</b>	<b>Chemical name</b>
5000 LBS	101-68-8	Diphenylmethane-4,4'- diisocyanate (MDI)

STATE REGULATIONS

State RTK	<b>CAS Number</b>	<b>Chemical name</b>
NJ	26447-40-5	Methylenediphenyl diisocyanate
MA, NJ, PA	101-68-8	Diphenylmethane-4,4'-diisocyanate (MDI)

## SECTION 16: OTHER INFORMATION

### Legend to abbreviations used in the safety data sheet:

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

### Abbreviation and acronyms:

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road
IMDG:	International Maritime Code for Dangerous Goods
DOT:	US Department of Transportation
IATA:	International Air Transport Association
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals
ACGIH:	American Conference of Governmental Industrial Hygienist.
EINECS:	European Inventory of Existing Commercial Chemical Substances
ELINCS:	European List of Notified Chemical Substance
CAS:	Chemical Abstracts Service (division of the American Chemical Society)
HMIS:	Hazardous Materials Identification System (USA)
WHMIS:	Workplace Hazardous Materials Information System (Canada)

### Further information/disclaimer

DISCLAIMER: The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigation to determine the suitability of information for their particular purposes. In no event shall Alchatek be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, whatsoever arising, even if Alchatek has been advised of the possibility of such damages.